



AS 502 HD

High Speed Double Needle Four Thread
Chain Stitch Bag Sewing Machine
for PP/HDPE WOVEN SACKS, LENO & PAPER BAGS



AS 502 HD



AS 502 PHD

SPECIAL FEATURES

- Specially designed for heavy weight material such as HDPE, PP, Multiwall, Paper and other types of woven sacks.
- Any type of cotton or synthetic yarn and plastic tape can be used.
- Easily convertible in single needle machine.
- Fully automatic lubrication with oil recycling system which ensures Long life of machine.
- Parts are easily available at very reasonable price.



TECHNICAL SPECIFICATIONS

Max. Speed	3,000 S.P.M.
Working Speed	Approx. 2800 r.p.m. (Depends on sewing material)
Seam	Twin-seam, each double thread chain stitch (2-needle, 2 looper, 4 thread type)
Distance between two needles	6 mm
Stitch length	11 to 18 stitches per 100 mm (adjustable)
Material thickness	Up to 8 mm
Kind of material	All types of woven sacks, hessian and multiwall paper bags
Needle Size	DN x 18, 25, 26 (Depends on thickness) / PP/HDPE Tape, Multifilament Yarn
Thread	Cotton, Synthetic
Motor	1/2 HP (Single / Three Phase) Clutch Motor 2850 R.P.M. Fully automatic 1 HP (Single / Three Phase) 1475 - 2850 R.P.M. (JHD)
Net Weight	50 kg.
Lubrication	Fully Automatic

Note: Can Replace Newlong / Union Special Sewing Head

For Food Grade Bags S.S. Cover of Sewing Machine & S.S. Cladding on wooden table top is available


ARMSTRONG

505, 'Sarpur' | Opp. Navjivan Press | B.H. Gujarat Vidyapith | Ahmedabad - 380 014 (India)
Tale: +91 79 3254 3747 | 3254 3551
Fax: +91 79 3254 3553
email: armstrong@stitchman.com | Web site: www.armstrongsewing.com



Since 1982
ARMSTRONG
"DO BUSINESS LIFELONG, WITH ARMSTRONG"

Sewing Machine for PP/HDPE Woven Sacks, Jute & Paper Bags & Fully Automatic Conversion Line



www.armstrongsewing.com

Fully Automatic Conversion Line



TECHNICAL SPECIFICATIONS

Diameter of Unwinding Cloth	1400 mm Maximum
Width of Unwinding Cloth	300 - 850 mm Applicable
Cutting Length	500 - 1400 mm Applicable
Cutting Length Accuracy	±1 mm
Production Capacity	30 - 50 bags / minute

MAIN FEATURES

- Equipped Two Servo Motor & 900 Transfer Grippers
- Fully Synchronized Central Control System with "Touch Screen" Operation.
- Excellent Performance with easy Operation
- Major Electrical Components (including Servo Motor, Servo Driven Inverter, Touch Screen Interface & Electrical switches) all adopt "Schneider" brand.

FULLY AUTOMATIC CUTTING - SEWING LINE

Model No.: CONVERTEC
(Cutting - Sewing)

Agent for:
India, Bangladesh & Nepal



AS 102 HS

High Speed Flat Bed Double Needle Four
Thread Chain Stitch Bag Sewing Machine
For AUTO BAG CONVERSION LINE - (BCS)

SPECIAL FEATURES

- Bearings are fitted in main shaft & Crank shaft Mechanism.
- Less Wear & Tear Due to Bearings.
- Improve Performance & Life of Machine.
- Parts are interchangeable with NL DKN 3W
- Parts are easily available at very reasonable price.

APPLICATION

- For Seaming of Light to Medium Weight Material.
- Most Suitable for PP/HDPE Woven Cloth Bags.

TECHNICAL SPECIFICATIONS

MAX. WORKING SPEED (R.P.M.)	STITCH RANGE SPEED (100 MM)	SEWABLE MATERIAL	NO. OF NEEDLE	NO. OF THREAD	DISTANCE BETWEEN TWO NEEDLES	NEEDLE SIZE	THREAD TYPE
3500 R.P.M.	11 - 14	PP/HDPE WOVEN CLOTH	TWO	FOUR	7 MM	UY 144 GS Nm 200/25	SYNTHETIC OR COTTON

Note: Can Replace Newlong / Union Special Sewing Head (Starlinger / Bothven / Golden Jason / Innova / Lohula)



NEWLONG



DKN - 3W GP

High Speed, Double Needle, Flat Bed,
Plain Feed, Double Thread Chain
Stitch Machine
For SEAMING & HEMMING OF PP WOVEN BAGS

MODEL	DKN3W GP	DKN3BP	DN3W	DN3HS
Max. Speed	4000 RPM	5000 RPM	3000 RPM	3000 RPM
Seam	Double Thread Chain Stitch (Type 401)			
Stitch Width	4.0-8.5 mm	5.0-9.5 mm	7-11 mm	7-12 mm
Bag Material	PP	PP	Paper-PP	Paper-PP
Thickness	Paper Bag 4P with Tuck			
Needle	UY144GS 200	UY144GS 200	UY143GS 200	DR x 2125
Oiling	Automatic	Automatic	Automatic	Automatic
Oil	Tellus # 32	Tellus # 32	Tellus # 32	Tellus # 32
Weight	28.5 kg	28.5 kg	28.5 kg	28.5 kg

AS 502 LHD



TECHNICAL SPECIFICATIONS
LEFT HAND SIDE DOUBLE NEEDLE,
FOUR THREAD, CHAIN STITCH
HIGH SPEED SEWING MACHINE.

APPLICATION

- Specially Designed for Auto Valve Making System.
- For Seaming of Light to Heavy Weight Fabrics such as PP/HDPE Woven Cloth.

TECHNICAL SPECIFICATIONS

MAX. SPEED (R.P.M.) APPROX.	WORKING SPEED (R.P.M.) APPROX.	STITCH RANGE (100 MM)	DISTANCE BETWEEN TWO NEEDLES	SEWING CAPACITY (mm)	NEEDLE SIZE	NO. OF NEEDLES	NO. OF THREAD	STITCHING THREAD TYPE	LUBRICATION
3000	2800 Depends on Sewing Material	11-18 *Adjustable	6 mm	Up to 8 mm	DN X 1 # 200/25 or DN X 1 # 230/26 (Croze-Becker)	Two	Four	PP/HDPE Tape Multi Filament / Fabricated Yarn	Fully Automatic